



The Alaska Wall Pack LED Light is your source of brilliance in architectural and outdoor lighting. This powerful fixture combines sleek design with high-performance LED technology, making it an ideal choice for illuminating building exteriors, pathways, and security areas.

With Alaska, you can trust in exceptional energy efficiency and lasting durability. Its cutting-edge LED technology delivers bright, consistent light while reducing energy consumption, saving you costs in the long run.

Designed to withstand the harshest elements, Alaska is a dependable lighting solution that shines through rain, snow, and heat. Whether you're enhancing safety, aesthetics, or functionality, Alaska's elegant presence and superior illumination make it the perfect choice for your outdoor lighting needs.

Ideal for use in Carparks, Garages, Parks, Yards and Walkways



GENERAL OVERVIEW							
CODE	HOUSING	LENS	WEIGHT (G)	WEIGHT (N)	LENGTH (A)	WIDTH (B)	DEPTH (D)
ALAS1001	Aluminium	Polycarbonate	4.5	4.3	319	165	265
ALAS1001E	Aluminium	Polycarbonate	6.5	6.3	319	165	265
ALAS1002	Aluminium	Polycarbonate	4.5	4.3	319	165	265
ALAS1002E	Aluminium	Polycarbonate	6.5	6.3	319	165	265

PRODUCT SPECIFICATION							
CODE	WATTAGE	LUMENS	EFFICIENCY	CCT	BEAM ANGLE	IP	IK
ALAS1001	13:18:28	1800 : 2500 : 3500	125	4k	120	65	10
ALAS1001E	13:18:28	1800 : 2500 : 3500	125	4k	120	65	10
ALAS1002	13:18:28	1800 : 2500 : 3500	125	4k	120	65	10
ALAS1002E	13:18:28	1800 : 2500 : 3500	125	4k	120	65	10

ELECTRICAL SPECIFICATION							
CODE	CHIP SET	DRIVER	PFC	COLOUR	VOLTAGE	CLASS	TEMPERATURE
ALAS1001	Lumiled	Tridonic	0.9	Black	220-240	I	-10° to + 35°
ALAS1001E	Lumiled	Tridonic	0.9	Black	220-240	I	-10° to + 35°
ALAS1002	Lumiled	Tridonic	0.9	Anthracite	220-240	I	-10° to + 35°
ALAS1002E	Lumiled	Tridonic	0.9	Anthracite	220-240	I	-10° to + 35°

ACCREDITATIONS & CERTIFICATION				
CODE	COUNTRY OF DESIGN	INTENDED MARKETS	APPROVALS	WARRANTY
ALAS1001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
ALAS1001E	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
ALAS1002	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
ALAS1002E	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year

