BERLIN BULKHEAD















The Berlin LED Bulkhead Light is your ultimate lighting solution for any environment. With unrivaled durability, it thrives in the toughest weather conditions, from torrential rain to extreme heat. Its robust construction is $perfect for high-traffic \, spaces, ensuring \, long evity \, in \, both \, outdoor \, and \,$ $indoor\,settings.\\$

Featuring energy-efficient LED technology, the Berlin light combines efficiency with reliability. Its sleek design seamlessly fits any space, adding security, ambiance, and illumination. Illuminate your surroundings with confidence, knowing that the Paris LED Bulkhead Light brings lasting performance and style to every setting. Your lighting needs, met with resilience and versatility. For Emergency -Add 'E' to Code For Dali Dimmable - Add 'D' to Code



NERAL OVERVIEW							
CODE	HOUSING	LENS	WEIGHT (G)	WEIGHT (N)	LENGTH (A)	WIDTH (B)	DEPTH (D)
BERLIN1001	Polycarbonate	Polycarbonate	1.5	1.2	302	302	67.5
BERLIN1002	Polycarbonate	Polycarbonate	1.5	1.2	302	302	67.5
BERLIN2001	Polycarbonate	Polycarbonate	2.0	1.7	352	352	67.5
BERLIN2002	Polycarbonate	Polycarbonate	2.0	1.7	352	352	67.5
DDUCT SPECIFICATIO	N						
CODE	WATTAGE	LUMENS	EFFICENCY	сст	BEAM ANGLE	IP	IK
BERLIN1001	14	1500	107	3k:4k	110	65	10
BERLIN1002	14	1500	107	3k:4k	110	65	10
BERLIN2001	22	2500	113	3k:4k	110	65	10
BERLIN2002	22	2500	113	3k:4k	110	65	10
CODE	CHIP SET	DRIVER	PFC	COLOUR	VOLTAGE	CLASS	TEMPERATURE
							TEITH EIGHTOILE
BERLIN1001	Limiled	Eaglerise	0.9	Black	220-240	II	-20° to + 40°
BERLIN1001 BERLIN1002	Limiled Limiled	Eaglerise Eaglerise	0.9	Black White	220-240 220-240	II II	
		· ·				==	-20° to + 40°
BERLIN1002	Limiled	Eaglerise	0.9	White	220-240	II	-20° to + 40° -20° to + 40°
BERLIN1002 BERLIN2001	Limiled Limiled Limiled	Eaglerise Eaglerise	0.9	White Black	220-240 220-240	II II	-20° to +40° -20° to +40° -20° to +40°
BERLIN1002 BERLIN2001 BERLIN2002	Limiled Limiled Limiled	Eaglerise Eaglerise	0.9	White Black White	220-240 220-240	II II II	-20° to +40° -20° to +40° -20° to +40°
BERLIN1002 BERLIN2001 BERLIN2002 CREDITATIONS & CER	Limiled Limiled Limiled TIFICATION COUNTRY	Eaglerise Eaglerise Eaglerise	0.9 0.9 0.9	White Black White	220-240 220-240 220-240	II II II	-20° to + 40° -20° to + 40° -20° to + 40° -20° to + 40°
BERLIN1002 BERLIN2001 BERLIN2002 CREDITATIONS & CER	Limiled Limiled Limiled TIFICATION COUNTRY	Eaglerise Eaglerise Eaglerise OF DESIGN	0.9 0.9 0.9 INTENDED	White Black White	220-240 220-240 220-240 APPRO	II	-20° to + 40°
BERLIN1002 BERLIN2001 BERLIN2002 CREDITATIONS & CER CODE BERLIN1001	Limiled Limiled Limiled TIFICATION COUNTRY United I	Eaglerise Eaglerise Eaglerise OF DESIGN	0.9 0.9 0.9 INTENDED UK: Euro	White Black White MARKETS	220-240 220-240 220-240 APPRO	0VALS 00598 - 2 - 1	-20° to + 40°







