



Clarity LED Downlights redefine lighting convenience and aesthetics. Ideal for both new build and retrofit projects, they offer high-performance illumination with effortless installation.

This versatile design ensures your lighting perfectly complements any decor.

With Clarity, you get the best of both worlds – brilliant lighting performance and a hassle-free installation process. Whether you're working on a contemporary project or revamping an existing space, Clarity LED Downlights are the stylish, practical choice that elevates your lighting experience. Illuminate your environment with Clarity and enjoy the perfect blend of form and function.

For Emergency - Add 'E' to Code
For Dali Dimmable - Add 'D' to Code



GENERAL OVERVIEW

CODE	HOUSING	LENS	WEIGHT (G)	WEIGHT (N)	OVERALL	CUTOUT	DEPTH (D)
CLARITY1001	Polycarbonate	Polycarbonate	1.1	0.9	145	120	65
CLARITY2001	Polycarbonate	Polycarbonate	1.3	1.1	174	150	65
CLARITY3001	Polycarbonate	Polycarbonate	1.3	1.1	232	200	100
CLARITY4001	Polycarbonate	Polycarbonate	1.5	1.3	232	200	100

PRODUCT SPECIFICATION

CODE	WATTAGE	LUMENS	EFFICIENCY	CCT	BEAM ANGLE	IP	IK
CLARITY1001	10	1100	100	4k	90	44	07
CLARITY2001	15	1650	100	4k	95	44	07
CLARITY3001	20	2400	100	4k	95	44	07
CLARITY4001	26	3120	100	4k	95	44	07

ELECTRICAL SPECIFICATION

CODE	CHIP SET	DRIVER	PFC	COLOUR	VOLTAGE	CLASS	TEMPERATURE
CLARITY1001	Lumiled	Eaglerise	0.9	White	220-240	I	-10° to + 40°
CLARITY2001	Lumiled	Eaglerise	0.9	White	220-240	I	-10° to + 40°
CLARITY3001	Lumiled	Eaglerise	0.9	White	220-240	I	-10° to + 40°
CLARITY4001	Lumiled	Eaglerise	0.9	White	220-240	I	-10° to + 40°

ACCREDITATIONS & CERTIFICATION

CODE	COUNTRY OF DESIGN	INTENDED MARKETS	APPROVALS	WARRANTY
CLARITY1001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
CLARITY2001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
CLARITY3001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
CLARITY4001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year

