

## **GUARDIAN EMERGENCY BULKHEAD**







The Guardian Emergency Bulkhead: Your Safety Sentry

The Guardian Emergency Bulkhead is your unwavering sentinel of safety. This reliable emergency lighting solution not only provides  $\label{eq:continuous} % \[ \begin{array}{c} (x,y) & (x,y) \\ (x,y) &$ peace of mind but also boasts a cost-effective and durable design.

The Guardian Emergency Bulkhead's unobtrusive, practical style fits seamlessly into a variety of environments, ensuring that you are wellprepared for unexpected situations.

With The Guardian Emergency Bulkhead, you benefit from both form and function without straining your budget. Elevate your safety standards with this bulkhead that not only safeguards your surroundings but also serves as a resilient and cost-effective  $emergency\ lighting\ solution.\ Illuminate\ your\ space\ with\ confidence,$ knowing that The Guardian Emergency Bulkhead has got you covered.



GENERAL OVERVIEW								
CODE	HOUSING	LENS	WEIGHT (G)	WEIGHT (N)	LENGTH (A)	WIDTH (B)	DEPTH (D)	
GUAR6001	Polycarbonate	Polycarbonate	2.1	1.9	351	111	63	
GUAR6001ST	Polycarbonate	Polycarbonate	2.1	1.9	351	111	63	
GUAR6002	Polycarbonate	Polycarbonate	3.9	3.7	321	167	83	
GUAR6002ST	Polycarbonate	Polycarbonate	3.9	3.7	321	167	83	

PRODUCT SPECIFICATION							
CODE	WATTAGE	LUMENS	EFFICENCY	ССТ	BEAM ANGLE	IP	IK
GUAR6001	3	150	50	6.5k	120	65	06
GUAR6001ST	3	150	50	6.5k	120	65	06
GUAR6002	10	1500	150	6.5k	135	65	08
GUAR6002ST	10	1500	150	6.5k	135	65	08

ELECTRICAL SPECIFICATIO	N						
CODE	CHIP SET	DRIVER	PFC	PRODUCT	VOLTAGE	CLASS	TEMPERATURE
GUAR6001	2835 LED	Seatronic	0.4	Standard	220-240	II	5° to + 40°
GUAR6001ST	2835 LED	Seatronic	0.4	Standard - Self Test	220-240	II	5° to + 40°
GUAR6002	2835 LED	Seatronic	0.3	Hgh Output	220-240	II	5° to + 45°
GUAR6002ST	2835 LED	Seatronic	0.3	High Output - Self Test	220-240	II	5° to + 45°

CODE	COUNTRY OF DESIGN	INTENDED MARKETS	APPROVALS	WARRANTY	
GUAR6001	United Kingdom	UK: Europe: UAE	CE: BS EN 60598 - 2 - 1	5 Year	
GUAR6001ST	United Kingdom	UK : Europe : UAE	CE: BS EN 60598 - 2 - 1	5 Year	
GUAR6002	United Kingdom	UK : Europe : UAE	CE: BS EN 60598 - 2 - 1	5 Year	
GUAR6002ST	United Kingdom	UK: Europe: UAE	CE: BS EN 60598 - 2 - 1	5 Year	

