



The Guardian Emergency Surface Round: Safety Redefined

The Guardian Emergency Surface Round sets a new standard in safety and reliability. This LED emergency spotlight, part of the Guardian series, combines modern aesthetics, quality, and affordability to bring you a truly outstanding safety solution.

Steek and stylish, The Guardian Emergency Surface Round seamlessly fits into any environment, adding an element of sophistication to your space while ensuring you are well-prepared for any emergency.

With The Guardian Emergency Surface Round, you get the perfect fusion of form and function without compromising your budget. Upgrade your safety standards with this spotlight that not only safeguards your surroundings but also elevates the overall aesthetic. Illuminate your space with both confidence and style, courtesy of The Guardian Emergency Surface Round.



GENERAL OVERVIEW

| CODE | HOUSING | LENS | WEIGHT (G) | WEIGHT (N) | LENGTH (A) | WIDTH (B) | DEPTH (D) |
|------------|---------------|---------------|------------|------------|------------|-----------|-----------|
| GUAR4001 | Polycarbonate | Polycarbonate | 0.8 | 0.7 | 155 | 155 | 46 |
| GUAR4001ST | Polycarbonate | Polycarbonate | 0.8 | 0.7 | 155 | 155 | 46 |
| GUAR4002 | Polycarbonate | Polycarbonate | 0.8 | 0.7 | 155 | 155 | 46 |
| GUAR4003 | Polycarbonate | Polycarbonate | 0.8 | 0.7 | 155 | 155 | 46 |
| GUAR4003ST | Polycarbonate | Polycarbonate | 0.8 | 0.7 | 155 | 155 | 46 |
| GUAR4004 | Polycarbonate | Polycarbonate | 0.8 | 0.7 | 155 | 155 | 46 |

PRODUCT SPECIFICATION

| CODE | WATTAGE | LUMENS | EFFICIENCY | CCT | BEAM ANGLE | IP | IK |
|------------|---------|--------|------------|------|------------|----|----|
| GUAR4001 | 2 | 270 | 135 | 6.5K | 150 | 65 | 03 |
| GUAR4001ST | 2 | 270 | 135 | 6.5K | 150 | 65 | 03 |
| GUAR4002 | 2 | 270 | 135 | 6.5K | 150 | 65 | 03 |
| GUAR4003 | 2 | 270 | 135 | 6.5K | 150 | 65 | 03 |
| GUAR4003ST | 2 | 270 | 135 | 6.5K | 150 | 65 | 03 |
| GUAR4004 | 2 | 270 | 135 | 6.5K | 150 | 65 | 03 |

ELECTRICAL SPECIFICATION

| CODE | CHIP SET | DRIVER | PFC | COLOUR | VOLTAGE | CLASS | TEMPERATURE |
|------------|----------|-----------|------|----------------------------|---------|-------|-------------|
| GUAR4001 | 5050 | Seatronic | 0.95 | White - Round | 220-240 | II | 5° to + 40° |
| GUAR4001ST | 5050 | Seatronic | 0.95 | White - Self Test - Round | 220-240 | II | 5° to + 40° |
| GUAR4002 | 5050 | Seatronic | 0.95 | Black - Square | 220-240 | II | 5° to + 40° |
| GUAR4003 | 5050 | Seatronic | 0.95 | White - Square | 220-240 | II | 5° to + 40° |
| GUAR4003ST | 5050 | Seatronic | 0.95 | White - Self Test - Square | 220-240 | II | 5° to + 40° |
| GUAR4004 | 5050 | Seatronic | 0.95 | Black - Square | 220-240 | II | 5° to + 40° |

ACCREDITATIONS & CERTIFICATION

| CODE | COUNTRY OF DESIGN | INTENDED MARKETS | APPROVALS | WARRANTY |
|------------|-------------------|-------------------|--------------------------|----------|
| GUAR4001 | United Kingdom | UK : Europe : UAE | CE : BS EN 60598 - 2 - 1 | 5 Year |
| GUAR4001ST | United Kingdom | UK : Europe : UAE | CE : BS EN 60598 - 2 - 1 | 5 Year |
| GUAR4002 | United Kingdom | UK : Europe : UAE | CE : BS EN 60598 - 2 - 1 | 5 Year |
| GUAR4003 | United Kingdom | UK : Europe : UAE | CE : BS EN 60598 - 2 - 1 | 5 Year |
| GUAR4003ST | United Kingdom | UK : Europe : UAE | CE : BS EN 60598 - 2 - 1 | 5 Year |
| GUAR4004 | United Kingdom | UK : Europe : UAE | CE : BS EN 60598 - 2 - 1 | 5 Year |