



The Guardian Eco Twin Spot redefines industrial lighting with a contemporary touch. This twin spotlight features a streamlined design, offering a polycarbonate body and head, making it an ideal choice for industrial applications.

The Guardian Eco Twin Spot embodies durability and efficiency. With advanced LED technology, it provides exceptional illumination, and its robust polycarbonate construction ensures long-lasting performance, even in the most demanding industrial settings.

Tailored for warehouses, factories, and manufacturing facilities, this twin spotlight is a reliable partner in creating a well-lit and safe workspace. Elevate your industrial lighting with The Guardian Eco Twin Spot, where style and practicality unite to deliver a lighting solution that surpasses others. Illuminate your industrial space with confidence.



GENERAL OVERVIEW

CODE	HOUSING	LENS	WEIGHT (G)	WEIGHT (N)	LENGTH (A)	WIDTH (B)	DEPTH (D)
GUAR1001	Polycarbonate	Polycarbonate	3.8	3.6	300	268	69
GUAR1001ST	Polycarbonate	Polycarbonate	3.8	3.6	300	268	69
GUAR1002	Polycarbonate	Polycarbonate	3.8	3.6	300	268	69
GUAR2001	Polycarbonate	Polycarbonate	4.2	4.0	300	268	69
GUAR2001ST	Polycarbonate	Polycarbonate	4.2	4.0	300	268	69
GUAR2002	Polycarbonate	Polycarbonate	4.2	4.0	300	268	69

PRODUCT SPECIFICATION

CODE	WATTAGE	LUMENS	EFFICIENCY	CCT	BEAM ANGLE	IP	IK
GUAR1001	4	500	125	6.5k	120	65	07
GUAR1001ST	4	500	125	6.5k	120	65	07
GUAR1002	4	500	125	6.5k	120	65	07
GUAR2001	9	1000	110	6.5k	120	65	07
GUAR2001ST	9	1000	110	6.5k	120	65	07
GUAR2002	9	1000	110	6.5k	120	65	07

ELECTRICAL SPECIFICATION

CODE	CHIP SET	DRIVER	PFC	COLOUR	VOLTAGE	CLASS	TEMPERATURE
GUAR1001	2835 LED	Seatronic	0.32	White	220-240	II	5° to +45°
GUAR1001ST	2835 LED	Seatronic	0.32	White - Self Test	220-240	II	5° to +45°
GUAR1002	2835 LED	Seatronic	0.32	Black	220-240	II	5° to +45°
GUAR2001	2835 LED	Seatronic	0.4	White	220-240	II	5° to +45°
GUAR2001ST	2835 LED	Seatronic	0.4	White - Self Test	220-240	II	5° to +45°
GUAR2002	2835 LED	Seatronic	0.4	Black	220-240	II	5° to +45°

ACCREDITATIONS & CERTIFICATION

CODE	COUNTRY OF DESIGN	INTENDED MARKETS	APPROVALS	WARRANTY
GUAR1001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
GUAR1001ST	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
GUAR1002	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
GUAR2001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
GUAR2001ST	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
GUAR2002	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year