



Experience illumination like never before with our Troffer Panel LED lights. These luminaires redefine your lighting solutions, blending elegance with modern functionality effortlessly.

The Troffer Panel LED lights deliver outstanding brightness while optimizing energy consumption. Their unique design fits seamlessly into various settings, from offices to retail spaces, offering ambient lighting that's both efficient and striking.

Illuminate your environment with confidence, knowing that Troffer Panel LED lights not only meet your aesthetic and functional needs but also elevate the visual appeal of your space. Discover the perfect fusion of style and efficiency with Troffer Panel LED Lighting, setting a new standard for exceptional lighting experiences.

Ideal for use in Corridors, Hospitals, Meeting Rooms, Reception Areas, Retail Environments and Schools



GENERAL OVERVIEW

CODE	HOUSING	LENS	WEIGHT (G)	WEIGHT (N)	LENGTH (A)	WIDTH (B)	DEPTH (D)
INIGMA1001	Aluminium	PMMA	3.8	3.5	595	595	115
INIGMA1001E	Aluminium	PMMA	4.5	4.2	595	595	115
INIGMA1001M	Aluminium	PMMA	3.9	3.6	595	595	115
INIGMA1001ME	Aluminium	PMMA	4.6	4.3	595	595	115

PRODUCT SPECIFICATION

CODE	WATTAGE	LUMENS	EFFICIENCY	CCT	BEAM ANGLE	IP	IK
INIGMA1001	30	3125	125	3.5k : 4k : 5k	145	20	06
INIGMA1001E	30	3125	125	3.5k : 4k : 5k	145	20	06
INIGMA1001M	30	3125	125	3.5k : 4k : 5k	145	20	06
INIGMA1001ME	30	3125	125	3.5k : 4k : 5k	145	20	06

ELECTRICAL SPECIFICATION

CODE	CHIP SET	DRIVER	PFC	PRODUCT	VOLTAGE	CLASS	TEMPERATURE
INIGMA1001	Lumiled	Tridonic	0.95	Standard	220-240	II	-30° to +40°
INIGMA1001E	Lumiled	Tridonic	0.95	Emergency	220-240	II	5° to +40°
INIGMA1001M	Lumiled	Tridonic	0.95	Microwave	220-240	II	-30° to +40°
INIGMA1001ME	Lumiled	Tridonic	0.95	Microwave Emergency	220-240	II	5° to +40°

ACCREDITATIONS & CERTIFICATION

CODE	COUNTRY OF DESIGN	INTENDED MARKETS	APPROVALS	WARRANTY
INIGMA1001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
INIGMA1001E	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
INIGMA1001M	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
INIGMA1001ME	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year

