



### The Pilot Pro Bulkhead: The Guiding Light in Modern Spaces

A LED luminaire inspired by the sleek efficiency of cockpit lighting. Crafted for reliability reminiscent of a seasoned pilot's instruments, this fixture is a testament to cutting-edge technology. Its aerodynamic silhouette seamlessly integrates into any space, providing clarity akin to an aircraft's guiding lights. With energy efficiency reaching new heights, let the Pilot Pro Bulkhead be your trusted co-pilot in creating the perfect ambience. Elevate your surroundings with this luminaire innovation and let your space take flight with style and efficiency.



#### GENERAL OVERVIEW

CODE	HOUSING	LENS	WEIGHT (G)	WEIGHT (N)	LENGTH (A)	WIDTH (B)	DEPTH (D)
PILOT1001	Steel Base	ABS Opal Diffuser	2.2	1.9	355	355	100
PILOT1001E	Steel Base	ABS Opal Diffuser	2.4	2.1	355	355	100
PILOT2001	Steel Base	ABS Opal Diffuser	2.8	2.5	435	435	100
PILOT2001E	Steel Base	ABS Opal Diffuser	3.1	2.8	435	435	100

#### PRODUCT SPECIFICATION

CODE	WATTAGE	LUMENS	EFFICIENCY	CCT	BEAM ANGLE	IP	IK
PILOT1001	22	1680	76	3k : 4k	115	20	07
PILOT1001E	22	1680	76	3k : 4k	115	20	07
PILOT2001	27	2850	106	3k : 4k	115	20	07
PILOT2001E	27	2850	106	3k : 4k	115	20	07

#### ELECTRICAL SPECIFICATION

CODE	CHIP SET	DRIVER	PFC	COLOUR	VOLTAGE	CLASS	TEMPERATURE
PILOT1001	Lumiled	Tridonic	0.9	White	220-240	I	-10° to + 40°
PILOT1001E	Lumiled	Tridonic	0.9	White	220-240	I	5° to + 40°
PILOT2001	Lumiled	Tridonic	0.9	White	220-240	I	-10° to + 40°
PILOT2001E	Lumiled	Tridonic	0.9	White	220-240	I	5° to + 40°

#### ACCREDITATIONS & CERTIFICATION

CODE	COUNTRY OF DESIGN	INTENDED MARKETS	APPROVALS	WARRANTY
PILOT1001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
PILOT1001E	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
PILOT2001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
PILOT2001E	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year