

### Prime Fire Rated Downlight: Safety Without Compromise

The Prime Fire Rated Downlight stands as a beacon of safety and innovation. Independently fire-tested for 30, 60, and 90 minutes, it surpasses industry standards, ensuring your peace of mind.

What sets Prime apart is its ground-breaking design—without intumescent materials. This not only enhances safety but also offers a cleaner, more sustainable choice for your lighting needs.

Equipped with loop-in loop-out push-fit terminals, Prime simplifies installation, saving you time and effort. Prime Fire Rated Downlight delivers uncompromising safety and ease without sacrificing performance. Illuminate with confidence, knowing your space is protected by the exceptional Prime Fire Rated Downlight.



### GENERAL OVERVIEW

CODE	HOUSING	LENS	WEIGHT (G)	WEIGHT (N)	OVERALL	CUTOUT	DEPTH (D)
PRIME1001	Steel	Polycarbonate	0.5	0.4	85	65	50
PRIME2001	Steel	Polycarbonate	0.5	0.4	85	65	50
PRIME3001	Steel	Polycarbonate	0.5	0.4	85	65	50

### PRODUCT SPECIFICATION

CODE	WATTAGE	LUMENS	EFFICIENCY	CCT	BEAM ANGLE	IP	IK
PRIME1001	6	600	100	3k : 4k : 5k	38	65	08
PRIME2001	6	600	100	3k : 4k : 5k	38	65	08
PRIME3001	6	600	100	3k : 4k : 5k	38	65	08

### ELECTRICAL SPECIFICATION

CODE	CHIP SET	DRIVER	PFC	COLOUR	VOLTAGE	CLASS	TEMPERATURE
PRIME1001	Lumiled	Eaglerise	0.9	White	220-240	II	-10° to +40°
PRIME2001	Lumiled	Eaglerise	0.9	Black	220-240	II	-10° to +40°
PRIME3001	Lumiled	Eaglerise	0.9	Satin Chrome	220-240	II	-10° to +40°

### ACCREDITATIONS & CERTIFICATION

CODE	COUNTRY OF DESIGN	INTENDED MARKETS	APPROVALS	WARRANTY
PRIME1001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
PRIME2001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
PRIME3001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year

