



### Simba Circular Suspended Pendant LED Light: Radiant Illumination

Introducing Simba, the circular pendant light that elevates your space. Crafted with precision and style, Simba offers a spectrum of coloured finishes too match your unique design vision. Its opal diffuser bathes your surroundings in a soft, inviting glow. What sets Simba apart? It is a bespoke light fitting, tailored to your individual preferences, making every Simba a unique masterpiece that will illuminate your space with both elegance and personality. Experience lighting that is as distinctive as you are with Simba.

Available Upon Request\*\*  
Code  
Add 'D' to Code

\*\*Any RAL Colour  
For Emergency - Add 'E' to  
For Dali Dimmable -



#### GENERAL OVERVIEW

CODE	HOUSING	LENS	WEIGHT (G)	WEIGHT (N)	LENGTH (A)	WIDTH (B)	DEPTH (D)
SIMBA1001	Aluminium	Polycarbonate	3.0	2.5	400	400	80
SIMBA1002	Aluminium	Polycarbonate	3.0	2.5	400	400	80
SIMBA2001	Aluminium	Polycarbonate	4.5	4.0	600	600	80
SIMBA2002	Aluminium	Polycarbonate	4.5	4.0	600	600	80
SIMBA3001	Aluminium	Polycarbonate	5.5	5.0	800	800	80
SIMBA3002	Aluminium	Polycarbonate	5.5	5.0	800	800	80
SIMBA4001	Aluminium	Polycarbonate	7.0	6.5	1000	1000	80
SIMBA4002	Aluminium	Polycarbonate	7.0	6.5	1000	1000	80

#### PRODUCT SPECIFICATION

CODE	WATTAGE	LUMENS	EFFICIENCY	CCT	BEAM ANGLE	IP	IK
SIMBA1001	20	2000	100	3k : 4k : 5k	110	20	06
SIMBA1002	20	2000	100	3k : 4k : 5k	110	20	06
SIMBA2001	40	4000	100	3k : 4k : 5k	110	20	06
SIMBA2002	40	4000	100	3k : 4k : 5k	110	20	06
SIMBA3001	60	6000	100	3k : 4k : 5k	110	20	06
SIMBA3002	60	6000	100	3k : 4k : 5k	110	20	06
SIMBA4001	80	8000	100	3k : 4k : 5k	110	20	06
SIMBA4002	80	8000	100	3k : 4k : 5k	110	20	06

#### ELECTRICAL SPECIFICATION

CODE	CHIP SET	DRIVER	PFC	COLOUR	VOLTAGE	CLASS	TEMPERATURE
SIMBA1001	Lumiled	Tridonic	0.95	Black	220-240	I	-10° to + 40°
SIMBA1002	Lumiled	Tridonic	0.95	White	220-240	I	-10° to + 40°
SIMBA2001	Lumiled	Tridonic	0.95	Black	220-240	I	-10° to + 40°
SIMBA2002	Lumiled	Tridonic	0.95	White	220-240	I	-10° to + 40°
SIMBA3001	Lumiled	Tridonic	0.95	Black	220-240	I	-10° to + 40°
SIMBA3002	Lumiled	Tridonic	0.95	White	220-240	I	-10° to + 40°
SIMBA4001	Lumiled	Tridonic	0.95	Black	220-240	I	-10° to + 40°
SIMBA4002	Lumiled	Tridonic	0.95	White	220-240	I	-10° to + 40°

#### ACCREDITATIONS & CERTIFICATION

CODE	COUNTRY OF DESIGN	INTENDED MARKETS	APPROVALS	WARRANTY
SIMBA1001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
SIMBA1002	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
SIMBA2001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
SIMBA2002	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
SIMBA3001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
SIMBA3002	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
SIMBA4001	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year
SIMBA4002	United Kingdom	UK : Europe : UAE	CE : BS EN 60598 - 2 - 1	5 Year